

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: TURBO MASTER LOK ΕΝΕΡΓΟΠΟΙΗΤΗΣ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: CarTell UK Ltd
56 Causeway Road
Earlstrees Industrial Estate
Corby
Northants
NN17 4DU
United Kingdom

Tel: +44 (0)15 3626 4222

Fax: +44 (0)15 3626 4333

Email: robert@cartell-uk.com

1.4. Emergency telephone number

Emergency tel: +44 (0)15 3626 4222
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Aquatic Chronic 2: H411; Flam. Aerosol 1: H222; -: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated
H315: Causes skin irritation.
H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS02: Flame
GHS07: Exclamation mark
GHS09: Environmental

SAFETY DATA SHEET

TURBO MASTER LOK ΕΝΕΡΓΟΠΟΙΗΤΗΣ

Page: 2



Precautionary statements: P211: Do not spray on an open flame or other ignition source.
P332+313: If skin irritation occurs: Get medical advice/attention.
P251: Do not pierce or burn, even after use.
P264: Wash hands thoroughly after handling.
P273: Avoid release to the environment.
P280: Wear protective clothing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

LOW BOILING POINT MODIFIED NAPHTHA - NAPHTHA (PETROLEUM), SOLVENT-REFINED LIGHT

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|------------|-----------|---|---------|
| 265-086-6 | 64741-84-0 | - | Asp. Tox. 1: H304; Flam. Liq. 1: H224; Skin Irrit. 2: H315; Aquatic Chronic 2: H411 | 30-50% |

PROPANE

| | | | | |
|-----------|---------|--|-------------------------------------|--------|
| 200-827-9 | 74-98-6 | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | 10-30% |
|-----------|---------|--|-------------------------------------|--------|

BUTANE

| | | | | |
|-----------|----------|--|-------------------------------------|--------|
| 203-448-7 | 106-97-8 | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | 10-30% |
|-----------|----------|--|-------------------------------------|--------|

ISOBUTANE

| | | | | |
|-----------|---------|--|-------------------------------------|-------|
| 200-857-2 | 75-28-5 | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | 1-10% |
|-----------|---------|--|-------------------------------------|-------|

N,N-DIMETHYL-P-TOLUIDINE

| | | | | |
|-----------|---------|---|--|-----|
| 202-805-4 | 99-97-8 | - | Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT RE 2: H373; Aquatic Chronic 3: H412 | <1% |
|-----------|---------|---|--|-----|

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

[cont...]

SAFETY DATA SHEET
TURBO MASTER LOK ΕΝΕΡΓΟΠΟΙΗΤΗΣ

Page: 3

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

[cont...]

SAFETY DATA SHEET
TURBO MASTER LOK ΕΝΕΡΓΟΠΟΙΗΤΗΣ

Page: 4

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PROPANE

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------------------|------------------------|------------|--------------|
| UK | 1800 mg/m ³ | 7200 mg/m ³ | - | - |

BUTANE

| | | | | |
|----|------------------------|------------------------|---|---|
| UK | 1450 mg/m ³ | 1810 mg/m ³ | - | - |
|----|------------------------|------------------------|---|---|

ISOBUTANE

| | | | | |
|----|------------------------|------------------------|---|---|
| UK | 2400 mg/m ³ | 9600 mg/m ³ | - | - |
|----|------------------------|------------------------|---|---|

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Colourless

[cont...]

SAFETY DATA SHEET
TURBO MASTER LOK ΕΝΕΡΓΟΠΟΙΗΤΗΣ

Page: 5

Odour: Characteristic odour

Evaporation rate: Fast

Oxidising: No data available.

Solubility in water: Not miscible

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Boiling point/range°C: No data available. **Melting point/range°C:** No data available.

Flammability limits %: lower: No data available. **upper:** No data available.

Flash point°C: -40 **Part.coeff. n-octanol/water:** No data available.

Autoflammability°C: >300 **Vapour pressure:** No data available.

Relative density: No data available. **pH:** Not applicable.

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

[cont...]

SAFETY DATA SHEET
TURBO MASTER LOK ΕΝΕΡΓΟΠΟΙΗΤΗΣ

Page: 6

N,N-DIMETHYL-P-TOLUIDINE

| | | | | |
|-----|-----|------|-----|-------|
| IPR | MUS | LD50 | 212 | mg/kg |
|-----|-----|------|-----|-------|

Relevant hazards for substance:

| Hazard | Route | Basis |
|---------------------------|-------|-----------------------|
| Skin corrosion/irritation | DRM | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

[cont...]

SAFETY DATA SHEET
TURBO MASTER LOK ΕΝΕΡΓΟΠΟΙΗΤΗΣ

Page: 7

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.
H222: Extremely flammable aerosol.
H224: Extremely flammable liquid and vapour.
H229: Pressurised container: May burst if heated
H301: Toxic if swallowed.
H304: May be fatal if swallowed and enters airways.
H311: Toxic in contact with skin.
H315: Causes skin irritation.
H331: Toxic if inhaled.
H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H411: Toxic to aquatic life with long lasting effects.
H412: Harmful to aquatic life with long lasting effects.

[cont...]

SAFETY DATA SHEET

TURBO MASTER LOK ΕΝΕΡΓΟΠΟΙΗΤΗΣ

Page: 8

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.